



ARCHITECTURAL SPECIFICATION:
 WALL PADDING TO BE MODEL- WP-26LU AS MANUFACTURED BY AK ATHLETIC EQUIPMENT, INC. IN COLUMBUS, OH. SIZE TO BE 2' WIDE BY 2 1/2" DEEP BY 7' HIGH WITH 1" LIP ON TOP AND BOTTOM OF EACH PANEL.
 PADS TO BE CONSTRUCTED USING 2" THICK 3.7 LB.DENSITY POLYURETHANE FOAM CEMENTED TO 7/16" OSB. COVER MATERIAL TO BE _____ (COLOR) 14 OUNCE POLYESTER LAMINATED VINYL STAPLED TO BACKING EVERY TWO INCHES.
 VINYL TO BE FLAME RETARDANT MATERIAL WHICH MEETS THE REQUIREMENTS OF CALIFORNIA FIRE MARSHALL. VINYL PASSES FLAME TEST ASTM E-84-87 AND IS RATED CLASS A FLAMESPREAD. IT MEETS THE REQUIREMENTS OF NFPA 701.
 CLASS "A" RATING TEST RESULTS ARE:
 * SMOKE DEVELOPMENT INDEX RATING OF 450 OR LESS
 * FLAME SPREAD INDEX OF 25 OR LESS
 VINYL IS PUNCTURE AND TEAR RESISTANT WITH MILDEW, ROT AND FUNGICIDE COMBATING PROPERTIES.
 COLOR AVAILABLE ARE: FLAIR RED, RICH RED, ROYAL BLUE, CHAMPION BLUE, NAVY BLUE, SKY BLUE, FOREST GREEN, KELLY GREEN, BLACK, CAMEL, WHITE, YELLOW, LIGHT GOLD, GREY, ORANGE, PURPLE, DARK MAROON, LIGHT MAROON AND BEIGE

DEALER:		CUSTOMER:	
PROJECT:		DATE:	
Date:		Approved by:	Drawn by: A. Katz.
MODEL: WP-26LU			
A K ATHLETIC EQUIPMENT, INC. COLUMBUS, OHIO 43213		Drawing number: 110	